



- (51) International Patent Classification<sup>7</sup>: G11B 7/013**
- (21) International Application Number: PCT/IB2004/052147**
- (22) International Filing Date: 20 October 2004 (20.10.2004)**
- (25) Filing Language: English**
- (26) Publication Language: English**
- (30) Priority Data: 03103999.3 29 October 2003 (29.10.2003) EP**
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).**

- (72) **Inventors; and**  
(75) **Inventors/Applicants (for US only):** IMMINK, Albert, H., J. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN DER LEE, Alexander, M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). BRULS, Dominique, M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). COENE, Willem, M., J., M. [BE/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) **Agent:** UITTENBOGAARD, Frank; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

*[Continued on next page]*

- (54) Title: RECORDING APPARATUS AND METHOD FOR RECORDING INFORMATION ON A RECORD CARRIER IN THE FORM OF CONTIGUOUS PIT-MARKS**



- (57) Abstract:** A recording apparatus for recording channel symbols of a channel data stream on a record carrier (50), said apparatus being adapted for recording said channel symbols as a channel band (cb) of at least two symbol rows (sr) one-dimensionally evolving along a first direction (t) and aligned with each other along a second direction (r), said two directions constituting a two-dimensional lattice of symbol cells (sc) each being associated with a symbol area (sa) of the record carrier (50). To reduce the occurrence of leading and trailing edges of pit-marks in the recorded channel band, and in order to be able to write a small radial extent in said second direction in view of limiting cross-write effects, it is proposed to record a channel symbols in the form of a mark area (rpm) having a longitudinal shape of a length in said first direction (l) substantially equal to the length of a symbol area (sa) in said first direction (t) and of a width in said second direction (r) being smaller than the width of a symbol area (sa) in said second direction (sa).